

ULTIMATE

Ultra High Solids Floor Finish

DESCRIPTION

A true advance in floor finish performance. This over 34% solids formula produces unmatched "off-the-mop" gloss with extended gloss retention. Utilizing exclusive MPS77 Polymer Technology, this superior floor coating will produce maximum gloss with fewer coats than conventional floor finishes. Combination sealer / finish saves product costs. Exceptional response to UHS burnishing. Applicable for use in high traffic areas; achieves maximum versatility. Maximum resistance to scratches and scuffs.

FEATURES / BENEFITS

- Applicable for use in high traffic areas; achieves maximum versatility
- MPS77 Polymer Technology produces exceptional gloss from fewer coats
- Sealer / finish Combination for product cost savings
- Maximum resistance to scratches and scuffs

SPECIFICATIONS

Type Pure acrylic polymers
Total Solids 34.5 ± .5%
pH..... 8.5 ± .5
Coverage..... 3000 sq. ft./gal
Drying Time 30 minutes

Color..... White, opaque liquid
Odor Typical acrylic
Film Appearance Clear
Powdering None
Flash Point None
Slip Resistant Yes

DIRECTIONS FOR USE

Floor Preparation: Using Stripper, strip off old finish and wax, paying particular attention to areas under furniture, and build-up areas. For baseboards and corners, use Baseboard Stripper. Remove all stripping solutions from floor with mop or wet dry vacuum. If necessary, rinse thoroughly with clean water and allow to completely dry.

Application: Using a clean mop or applicator apply a thin uniform coat of finish. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more than 4 coats in a 24 hour period. Floor should be thoroughly dry before traffic is allowed in area.

High Speed Buffing and Burnishing: This is an ideal product for use with high speed polishing or burnishing machines of 1500 RPM or higher. Allow 24 hours after finishing floor before attempting to burnish. Prior to high speed buffing or burnishing the floor surface should be dust mopped using Dust Mop Treatment. When buffing or dry burnishing use an aggressive natural Buffing Pad. To restore floor finish, use approved buffing compound. Follow label directions for proper dilution and use.

Maintenance: Maintain by dust mopping daily using mop treated with Dust Mop Treatment. Damp mop or clean with an automatic scrubber as required, using a neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended using use approved buffing compound. Worn areas, or the entire floor, may be re-coated as required to maintain a uniform high gloss. When stripping becomes necessary, use approved floor finish stripper.

SAFETY INFORMATION

CAUTION: MAY BE HARMFUL IF SWALLOWED KEEP OUT OF REACH OF CHILDREN

HMIS HAZARD CODE: HEALTH:1 FLAMMABILITY:0 REACTIVITY:0 OTHER:0

Avoid eye contact. Do not ingest. For Eyes: Flush thoroughly with water for 15 minutes. Get medical aid.

If Ingested: Induce vomiting. Give large quantities of water. Get medical aid.

Meets or exceeds CSMA and ASTM slip resistance standards of 0.5 minimum as determined by ASTM D-2047.



INSCO, Inc.

Performance Driven Sanitary Maintenance Products

1611 Ralston Street • Wilson, NC 27893

(252) 291-0102 • FAX (252) 291-8439

(800) 849-1133

MATERIAL SAFETY DATA SHEET
(SIMILAR TO OSHA FORM 174)

N.A.=Not Applicable
Not Est.=Not Established
Prop.=Proprietary

SECTION 1-MANUFACTURER/DISTRIBUTOR INFORMATION

Product Name: ULTIMATE Ultra High Solids Floor Finish
Supplier's Name: INSCO, Inc.
Supplier's Address: 1611 Ralston Street, Wilson, NC 27893
HMIS Hazard Code: Health:1 Flammability:0 Reactivity:0 Other:0
Chemical Family: Floor Finish
D.O.T. Shipping Name: N/A

Emergency Phone #:(800) 255-3924
Chemical Name: Acrylic Latex Blend
Formula: N.A. Blended Product
Hazard Class: N/A **D.O.T. ID#:** N/A

SECTION 2-HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS NO.	% Concentrate Range	Hazard Ratings (TLV/PEL)
None			

SECTION 3-PHYSICAL DATA

Boiling Point (F): 212°
Vapor Pressure: = To Water
Vapor Density: = To Water
Solubility In Water: Disperses
Appearance: White, Opaque
Liquid
Odor: Characteristically Acrylic

Specific Gravity: 1.029
Evaporation Rate: = To Water

SECTION 4-FIRE AND EXPLOSION DATA

Flash Point (F): None To Boiling (TOC)
Flammable Limits: N.A.
Unusual Fire & Explosion Hazards: Heated material may liberate toxic fumes. Wear self contained breathing apparatus.

SECTION 5-HEALTH HAZARD DATA

Route(s) of Entry: Inhalation:No Skin:Yes Ingestion:Yes **Threshold Limit Value:** Not Est.
Effects of Overexposure: May cause skin and eye irritation. If ingested, may cause severe gastric distress and blockage.
Emergency & First Aid Procedures: **For Eyes:** Flush with water for at least fifteen minutes. If irritation persists get medical aid. **For Skin:** Wash with soap and water. **If Ingested:** Induce vomiting. Get medical aid.
Conditions Aggravated by Exposure: None

Listed Carcinogen, Mutagen, Teratogen (Ingredient, Source, Amount): None

SECTION 6-REACTIVITY DATA

Stability: Stable
Conditions to Avoid: None
Incompatibility: Avoid Contact with Strong Acids and Oxidizers.
Hazardous Decomposition Products: Carbon Oxides and Acrylates
Hazardous Polymerization: Will not occur.

SECTION 7-SPILL OR LEAK PROCEDURES

Steps to be taken if material is released or spilled:
Recontainerize by mopping, wet vacuum, or using a suitable absorbent.
Waste disposal method: Follow local, state, and federal regulations.

SECTION 8-SPECIAL PROTECTION INFORMATION

Respiratory Protection: Not required.
Ventilation: Local.
Protective Gloves: Not Required.
Eye Protection: Safety Glasses.
Other Protective Equipment: None.

SECTION 9-SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Store between 40° and 140° F. Do not freeze.
Other Precautions: Keep out of reach of children. For sale to, use and storage by service personnel only.

The information contained in this MSDS was obtained from current and reliable sources, however the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of this company, it is not responsible for loss, injury and expense arising out of the product's improper use. No warranty, expressed or inferred, regarding the product described in this MSDS shall be created or inferred by any statement in this MSDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.