

MATERIAL SAFETY DATA SHEET
COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

SECTION I · PRODUCT IDENTIFICATION

Product Name: STE-POL Stainless Steel Cleaner
Product Number: 14014
Product Type: AEROSOL
Formula: Proprietary
Supplier's Name: INSCO
Supplier's Address: P.O. Box 2065, Wilson, NC 27894-2065
DOT Ship Description: CONSUMER COMMODITY, ORM-D

Date Prepared: 11/15/2007
Information Phone: (252) 291-0102
Emergency Phone: (800) 535-5053

HMS Rating (Based on Aerosol Conc.):
0-Minimal 1-Slight 2-Moderate
3-Serious 4-Extreme

| | |
|-----------------------------|---|
| HEALTH: | 1 |
| FLAMMABILITY: | 3 |
| PHYSICAL HAZARD: | 0 |
| Personal Protection: | B |

SECTION II · INGREDIENTS

| CHEMICAL NAME | CAS # | %WT | 313/Chem | Skin | Carcinogen | PEL | TLV-TWA |
|---------------------------|--------------|------------|-----------------|-------------|-------------------|------------|----------------|
| White Mineral Oil | 8042-47-5 | 35-45 | NO | NO | NO | 5 mg/m3* | 5 mg/m3* |
| Acetone | 67-64-1 | 5-15 | NO | NO | NO | 1000 ppm | 500 ppm |
| Isoparaffinic Hydrocarbon | 64741-66-8 | 1-10 | NO | NO | NO | N/E | 281 ppm** |
| Liquefied Petroleum Gas | 68476-86-8 | 20-30 | NO | NO | NO | 1000 ppm | 1000 ppm |

*exposure limits for mist

**manufacturer's Recommended Exposure Limit (REL)-TWA

SECTION III · PHYSICAL DATA

Aerosol Concentrate:
Boiling Point: 120 °F
pH: N/A
Appearance/Odor: Clear, colorless liquid with mint odor

Specific Gravity (H₂O=1)@70 °F: 0.825
Solubility In Water: negligible
Vapor Density(Air=1): >1

Total Contents:
Total VOC %: 30.12%
Vapor Pressure (can; psig @72 °F): 50

SECTION IV · FIRE AND EXPLOSION DATA

Flash Point (Conc.): <2 °F (TCC)
Extinguishing Media: Foam, CO₂, Dry Media
Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.
Unusual Fire and Explosion Hazards: Exposure to temperature above 120 °F may cause bursting.

Flammability (as per CSMA Flame Projection Test): Extremely-Flammable Spray

SECTION V · REACTIVITY DATA

Stability: Material Stable.
Incompatibility: Avoid contact with strong oxidizing agents, chloroform, alkalis, chlorine compounds, acids, and potassium t-butoxide.
Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxides.

Hazardous Polymerization: Will not Occur.

SECTION VI · STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN.
For Industrial and Institutional use only.
Store in a cool, dry area away from heat or open flame.
Do not store at temperatures above 120 °F.

NFPA Code 30B Rating: Level 3 Aerosol.

SECTION VII · HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: May cause moderate to severe irritation accompanied by stinging, tearing, redness, blurred vision, and pain.
Skin: Frequent or prolonged contact may cause irritation and possibly dermatitis. May aggravate existing skin conditions.
Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, anesthesia, dizziness, headache, rapid breathing, narcosis, and other central nervous system effects, including unconsciousness and death.
Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause severe pulmonary injury, possibly progressing to death.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.
Skin: Wash with soap and water. If irritation persists seek medical attention.
Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.
Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII · SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions.
Ventilation: Provide local exhaust to keep concentration of Section II ingredients below acceptable limits.
Protective Gloves: Use chemical resistant gloves if hand contact will be made.
Eye Protection: Always wear safety glasses or chemical proof goggles when working with chemicals.

SECTION IX · SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.